

Amendments to the Claims:

Claims 2 and 4 are amended, claim 15 is cancelled and claims 26 to 29 are added as set forth hereinafter.

Listing of Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application.

1. (Original) An arrangement for holding a camera rearward of an ocular of a glass in the form of a monocular or a binocular, the arrangement comprising:

5 a mount for holding said camera rearward of said ocular of said glass;

an attachment element on said glass whereat said glass can be connected to a stand; and,

10 a base connected to said mount and having an attachment device for attaching said base to said glass at said attachment element.

2. (Currently Amended) The arrangement of claim 1, wherein said attachment element is a first attachment element and said base ~~having~~ has a base attachment element formed therein whereat said arrangement can be connected to a stand.

3. (Original) The arrangement of claim 2, said base attachment element being shifted in the direction of said ocular with

reference to said first attachment element.

4. (Currently Amended) The arrangement of claim 2, wherein said camera, said glass and said arrangement conjointly define a system having a center of gravity; and, said base has a plurality of said base attachment elements formed therein whereat said
5 arrangement can be connected to a stand; and, said base attachment elements ~~being~~ are formed in said base so that always one of said base attachment elements is disposed in the region of said center of gravity.

5. (Original) The arrangement of claim 1, wherein said camera is connected to said base via a joint.

6. (Original) The arrangement of claim 5, wherein said joint is a rotational joint.

7. (Original) The arrangement of claim 6, wherein said rotational joint has at least one detent position.

8. (Original) The arrangement of claim 6, wherein said rotational joint has a plurality of detent positions.

9. (Original) The arrangement of claim 6, wherein said ocular defines an optical axis and said rotational joint defines a rotational axis; and, said optical axis and said rotational axis conjointly define an angle.

10. (Original) The arrangement of claim 2, wherein said camera is connected to said base via a rotational joint; and, said rotational joint lies between said base attachment element and a vertical from the end surface of said ocular.

11. (Original) The arrangement of claim 1, further comprising a length adjusting device for changing the horizontal distance between said mount and said attachment device.

12. (Original) The arrangement of claim 11, further comprising an elevation adjusting device for varying the vertical distance between said base and said mount.

13. (Original) The arrangement of claim 12, further comprising a lateral adjusting device for adjusting the position of the objective of said camera relative to said ocular.

14. (Original) The arrangement of claim 1, wherein said mount includes a latchable ball joint connection for facilitating a parallel alignment of the objective of said camera and said ocular.

15. (Cancelled).

16. (Original) An arrangement for holding a camera rearward of an ocular of a glass in the form of a monocular or a binocular, the arrangement comprising:

a base attached to said glass;

5 said base including a ball joint; and,
 means connected to said ball joint for pivoting said camera
away from said ocular.

17. (Original) An arrangement for holding a camera rearward of
an ocular of a glass in the form of a monocular or a binocular,
the arrangement comprising:

 a base;

5 a mount for holding said camera rearward of said ocular of
said glass;

 an attachment device for tightly mounting said base relative
to said glass;

 said mount and said base conjointly defining an interface;

10 and,

 a joint arranged at said interface for facilitating a
pivoting of said camera away from said ocular.

18. (Original) The arrangement of claim 17, wherein said joint
is a rotational joint.

19. (Original) The arrangement of claim 18, wherein said
rotational joint has at least one detent position.

20. (Original) The arrangement of claim 18, wherein said
rotational joint has a plurality of detent positions.

21. (Original) The arrangement of claim 18, wherein said ocular
defines an optical axis and said rotational joint defines a

rotational axis; and, said optical axis and said rotational axis conjointly define an angle.

22. (Original) The arrangement of claim 17, further comprising a length adjusting device for changing the horizontal distance between said mount and said attachment device.

23. (Original) The arrangement of claim 22, further comprising an elevation adjusting device for varying the vertical distance between said base and said mount.

24. (Original) The arrangement of claim 23, further comprising a lateral adjusting device for adjusting the position of the objective of said camera relative to said ocular.

25. (Original) The arrangement of claim 17, wherein said mount includes a latchable ball joint connection for facilitating a parallel alignment of the objective of said camera and said ocular.

26. (New) An arrangement of a camera and a glass in the form of a monocular or binocular having an ocular with said ocular defining an optical axis, the arrangement comprising:

5 a holder for holding said camera rearward of and in spaced relationship to said ocular; and,

means for pivoting said holder and said camera about a point lying approximately on said optical axis.

27. (New) An arrangement of a camera and a glass in the form of a monocular or binocular having an ocular with said ocular defining an optical axis, the arrangement comprising:

a holder for holding said camera rearward of said ocular;

5 means for pivoting said holder and said camera about a rotational axis; and,

said rotational axis and said optical axis of said ocular conjointly defining an angle.

28. (New) The arrangement of claim 27, wherein said angle is an acute angle; and, said pivoting means pivots said holder and said camera to move said camera away from behind said ocular.

29. (New) An arrangement of a camera and a glass in the form of a monocular or binocular having an ocular with said ocular defining an optical axis, the arrangement comprising:

a holder for holding said camera rearward of said ocular;

5 means for pivoting said holder and said camera about a rotational axis;

said rotational axis and said optical axis of said ocular conjointly defining an angle; and,

said camera and said holder being pivoted about a point
10 which lies approximately on said optical axis of said ocular.